



KRISH
BIOMEDICALS

An ISO 9001:2008 Company

XC-A30

● ESR Analyzer





XC-A30

● ESR Analyzer



Features

- Random access
- Up to 30 samples can be scanned simultaneously
- Throughput: up to 60 samples /hour
- Temperature compensation refer to 18 °C according to Westergren method
- ESR curve display and print-out
- Touch screen , large LCD display
- Built-in Internal thermal recorder



Specifications

Area of application	Erythrocyte sedimentation rate analysis
Measuring principle	Infrared sensor
Reading channels	30 available channels
Loading capability	Up to 30 samples at a time
Loading pattern	Random
Measuring time	30 minutes or 60 minutes selectable
Throughput	Up to 60 samples per hour
Analysis result	In Westergren ESR value (mm / hr)
Temperature compensation	Refer to 18°C automatically (selectable)
Reading resolution	0.2 mm
Reproducibility	< 0.3% or ±2mm /1h
Result resolution	1mm/1h
Blood level range	50mm-64mm
Display	LCD screen with backlight

Input	Touch screen
Interface	RS-232 serial port
Print	Internal thermal recorder
Power supply	AC 220V/110V ±10%, 50/60 Hz, 50W
Operation conditions	Temperature 15°C~32°C Humidity≤85%
Dimension	400mmx300mmx200mm(LxWxH)
Net weight	11.5kg



KRISH BIOMEDICALS

T-7& S-35, 35, Panikaj Central Market, I.P. Extn., Patparganj, New Delhi - 110092, INDIA
 Tel: 91 11 42175285, 42648385, Fax: 91 11 42175785 Mob: 91 09999766100, 9958646413
 Email: sales@krishbiomedicals.com website: www.krishbiomedicals.com